www.yellowbusdecals.com



SCHOOL BUS sign	Yes	No
LOCATED ABOVE FRONT WINDSHIELD		
LOCATED ABOVE REAR WINDOWS		
NOT LESS THAN 8 INCHES IN HEIGHT		
GOOD LEGIBLE CONDITION		
STOP WHEN RED LIGHTS FLASH		
LOCATED ON REAR OF BUS, BELOW WINDOWS		
PLAINLY VISIBLE		
LETTERING IS AT LEAST 6 INCHES IN HEIGHT		
LETTERING IS 6" FROM ANY MANUFACTURER LOGO OR SIGN		
LETTERING IS 6" AWAY FROM ANY BUS UNIT NUMBER		
GOOD LEGIBLE CONDITION		
CARRIER NAME		
LOCATED BELOW SIDE WINDOWS		
(PROJECT) NO LESS THAN 4" AND NO MORE THAN 6" IN HEIGHT		
STYLE OF LETTERING IS READABLE AT 50 FEET		
LETTERING IS 6" AWAY FROM ANY MANUFACTURER LOGO		
LETTERING IS 6" AWAY FROM ANY BUS UNIT NUMBER		
LETTERING IS 12" AWAY FROM ANY ADDITIONAL SIGNS*1		
NO ADDRESSES, TELEPHONE NUMBERS, STRIPES, SLOGANS, GRAPHICS		
GOOD LEGIBLE CONDITION		

^{* 1} Additional Signs are signs consisting of numbers, letters or illustrations with contents limited to special identification, busrouting information, warning against unauthorized entry, or sign of sponsor's donation of a school bus. They are placed on side of bus below passenger window.

www.yellowbusdecals.com



CARRIER ID NUMBER (CA Number)	Yes	No
LOCATED CENTER OF CARRIER NAME		
LOCATED WITHIN 24" OF CARRIER NAME		
PROJECT AT LEAST 2" HEIGHT		
GOOD LEGIBLE CONDITION		
UNIT BUS NUMBERS		
LOCATED ON REAR OF BUS BELOW PASSENGER WINDOW GLASS		
LOCATED ON FRONT OF BUS BELOW PASSENGER WINDOW GLASS		
1 LOCATED ON EACH SIDE		
(OPTIONAL) IF OVER 30FT- 2 CAN BE LOCATED ON EACH SIDE *2		
(OPTIONAL) BUS BUILT BEFORE 1-1992 CAN BE ON ALL 4 CORNERS		
ALL NUMBERS PROJECT A HEIGHT OF AT LEAST 4"		
LETTERING 6" AWAY FROM ANY MANUFACTURER LOGO OR BUS SIGN		
LETTERING IS 12 INCHES AWAY FROM ANY ADDITIONAL SIGNS*1		
GOOD LEGIBLE CONDITION		
EMERGENCY EXIT LABELING EXTERIOR		
ALL EMERGENCY WINDOWS ARE LABELED		
EMERGENCY EXIT LABEL LOCATED AT TOP OR ABOVE EMERGENCY EXIT		
LETTERING IS BLACK		
BACKGROUND IS NSBY or WHITE IF LOCATED ON PAINTED WHITE ROOF		
* 1 Additional Signs are signs consisting of numbers, letters or illustrations with contents limited to special identification	n.busrouting informa	ation.

warning against unauthorized entry, or sign of sponsor's donation of a school bus. They are placed on side of bus below passenger window.

^{* &}lt;sup>2</sup> Front number as far forward as possible, rear number as far to rear as possible

www.yellowbusdecals.com



EMERGENCY EXIT LABELING EXTERIOR (CONT.)	Yes	No
LETTERING IS PROJECTED AT 2" IN HEIGHT		
WINDOW EXITS OUTLINED IN 1" RETROREFLECTIVE TAPE		
GOOD LEGIBLE CONDITION		
ALL EMERGENCY DOORS ARE LABELED		
EMERGENCY EXIT LABEL LOCATED AT TOP OR ABOVE EMERGENCY DOOR		
LETTERING IS BLACK		
BACKGROUND IS NSBY (WHITE IF LOCATED ON PAINTED WHITE ROOF)		
LETTERING IS PROJECTED AT 2" IN HEIGHT		
DOOR EXITS OUTLINED IN 1" RETROREFLECTIVE TAPE		
ARROWS AND OPERATING INSTRUCTIONS AT ALL EMERGENCY EXITS		
INSTRUCTIONS ARE BLACK LETTERING, CONTRAST BACKGROUND		
ROOF HATCH IS OUTLINED IN 1" REFLECTIVE		
ROOF HATCH IN LABELED FOR EMERGENCY EXIT		
GOOD LEGIBLE CONDITION		
EMERGENCY EXIT LABELING INTERIOR		
"EMERGENCY EXIT" OR "EMERGENCY DOOR" LETTERS 2" HEIGHT		
LOCATED AT TOP OR ABOVE EACH EMERGENCY EXIT		
LETTERING CONTRAST WITH BACKGROUND		
CONCISE INSTRUCTIONS FOR OPERATING EACH EMERGENCY EXIT		
* ³ Roof hatch "Emergency Exit" letters have no color or height requirement as long as they have manufacturers operating	; instructions	

Courtesy www.yellowbusdecals.com

page 3



page 4

www.yellowbusdecals.com	ue	Cais
EMERGENCY EXIT LABELING INTERIOR(CONT.)	Yes	No
OPERATING INSTRUCTION LETTERING CONTRASTS WITH BACKGROUND		
OPERATING INSTRUCTIONS LETTERING MINIMUM 1/2" HEIGHT		
OPERATING INSTRUCTIONS ARE WITHIN 6" OF RELEASE MECHANISM		
"DO NOT BLOCK" LABEL AT TOP OR ABOVE ALL EMERGENCY EXITS		
"DO NOT BLOCK" LETTERING AT LEAST 1" IN HEIGHT *4		
* ⁴ "DO NOT BLOCK" signs are needed on buses that have 2 or more wheelchair anchorage points		
NOTES		
A WEIGH		A
	511	
decais		

Courtesy www.yellowbusdecals.com